

**SMOKE AND CLEAN AIR GENERATING MACHINE FOR  
DETECTING THE PRESENCE AND LOCATION OF  
LEAKS IN A FLUID SYSTEM**

**BACKGROUND OF THE INVENTION**

**1. Field of the invention.**

This invention relates to a compact, easy to use and portable smoke and clean air generating machine that enables the presence and location of leaks in a fluid system (e.g. the evaporative or brake system of a motor vehicle) to be accurately and visually detected depending upon the rate of air flow through the fluid system under test and whether smoke escapes from the system.

**2. Background art.**

Our Patent Application No. 09/020,841 filed February 9, 1998 and entitled SMOKE PRODUCING APPARATUS FOR DETECTING LEAKS IN A FLUID SYSTEM discloses an efficient, portable apparatus for generating smoke in order to locate leaks in a fluid (e.g. air, oil, fuel, exhaust, etc.) system. A supply of oil within a sealed chamber is vaporized, and the resulting smoke is delivered to the system under test. By visually inspecting the system for smoke escaping therefrom, the precise location of a leak in the system can be accurately detected.

With the growing emphasis being placed on reducing the volume of emissions leaking into the atmosphere, it has become increasingly important to be able to monitor



and test the integrity of a fuel vapor recovery or evaporative system in today's motor vehicles. By way of example, to test for leaks, the evaporative system of a motor vehicle is typically pressurized for a predetermined time. If the pressure holds throughout the time interval, then the integrity of the system is presumed to be intact.

5

The problem is that this conventional method of testing for leaks in the vapor recovery system of a motor vehicle does not take into account the volume of fuel stored in the gas tank. That is to say, the smaller the volume of fuel stored in the gas tank, the greater will be the empty space within the tank lying above the fuel supply. Such empty space acts an air and pressure accumulator. More particularly, for a vehicle with less fuel and a larger air space in its tank, it will take a longer time to detect a leak. Therefore, the test operator can receive a false indication as to the integrity of the evaporative system, because of the increased time that is required for this system having an air accumulator to be fully pressurized. Consequently, an evaporative system which shows that it is holding pressure over time may actually have a leak and be in need of repair to avoid emissions to the atmosphere.

Accordingly, it is desirable to be able to overcome the aforementioned problems associated with the conventional method of testing for leaks in a fluid system so that the existence and location of a leak may be accurately verified and detected. To this end, it would also be desirable to achieve this goal by using the efficient smoke generating apparatus that is described in our above-entitled patent application.

3

## SUMMARY OF THE INVENTION

Briefly, and in general terms, a smoke and clean air generating machine is disclosed that is adapted to produce either a supply of clean air or a supply of smoke to a fluid system (e.g. the evaporative or brake system of a motor vehicle) to be tested for leaks. An air compressor provides a supply of air under pressure. The air compressor is connected to supply air to a smoke generating apparatus or to a flow meter by means of a two-way bleed off selector valve. More particularly, with the selector valve rotated to a clean air position, the air compressor will communicate with the flow meter which measures the rate of air being delivered to the system under test. With the selector valve rotated to a smoke position, the air compressor will be connected to the smoke generating apparatus so that a supply of oil in a sealed chamber can be blown towards and vaporized by a heating grid and the resulting smoke delivered to the system under test. However, when the selector valve passes through a center position between its smoke position and clean air position, any pressure that has been developed in the air line between the air compressor and the smoke generating apparatus will be exhausted (i.e. bled off) to the atmosphere so as to automatically de-energize the heating grid of the smoke generating apparatus and thereby insure that the heating grid will cool and no additional smoke will be generated.

In operation, the selector valve is first rotated to its clean air position, whereby a supply of clean (i.e. non-smoky) air is delivered from the air compressor to the system under test via the flow meter. An air accumulator having an integral check valve to relieve excess pressure is located between the selector valve and the flow meter to

smooth any pulsations in the flow of air to the meter. The existence of a leak having sufficient size to require repair is indicated in the event that the flow meter reads a rate of air flow from the air compressor to the system under test which is greater than a predetermined flow rate that is characteristic of a leak free system. Should a leak be indicated, the selector valve is then rotated to its smoke position, whereby a supply of air is delivered from the air compressor to the smoke generating apparatus. The smoke generating apparatus generates a supply of smoke via a smoke outlet line thereof to the fluid system under test. By visually inspecting the system under test for any escaping smoke, the precise location of a leak can be determined. Coupled to the smoke outlet line of the smoke generating apparatus is a pressure discharge accumulator having an integral check valve that is adapted to open to relieve excess pressure. In the event of a pressure build-up in the smoke outlet line (such as when the system to be tested is partially or completely restricted), the smoke is diverted to the check valve. As the exiting smoke begins to cool and condense, droplets of oil will be collected within the pressure discharge accumulator. The excess pressure within the smoke outlet line will then be dissipated to the atmosphere through a small orifice in the accumulator.

As an alternate embodiment of the present invention, the air compressor to deliver clean air to the flow meter and the smoke generating apparatus can be replaced by a pressure and flow regulated source of non-flammable nitrogen gas. In this case, a mixture of nitrogen (rather than air) and smoke will travel through the smoke outlet line to be delivered to the system under test so that a relatively safe, non-explosive

5

environment can be established, particularly in situations characterized by high temperatures.

5. BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a schematic of the smoke and clean air generating machine which forms the present invention for verifying the presence and detecting the location of leaks in a fluid system under test;

10

FIG. 2 shows a 2-way selector valve from the smoke and clean air generating machine of FIG. 1 rotated to a clean air position for connecting an air compressor to the fluid system under test by way of a flow meter;

15

FIG. 3 illustrates the selector valve of FIG. 2 rotated to a smoke position to connect the air compressor to a smoke generating apparatus; and

FIG. 4 shows the selector valve rotated to a center position between the clean air and smoke positions of FIGs. 2 and 3 for discharging pressure through the selector valve to control the operation of the smoke generating apparatus.

20

DETAILED DESCRIPTION

25 Referring to the drawings, there is shown in FIG. 1 a smoke and clean air generating machine having an outer casing (designated by phantom lines) 50 within which is housed a smoke generating apparatus 1 that is adapted to generate a supply of

6

smoke to a smoke outlet line 2 and a smoke supply line 4 so that a fluid system (not shown) can be visually inspected for leaks. The smoke generating apparatus 1 has been described in detail in our earlier Patent Application Serial No. 09/020,841 filed February 9, 1998, the teachings of which are incorporated herein by reference. Therefore, a full  
5 description of the smoke generating apparatus 1 will not be provided.

Briefly, however, the smoke generating apparatus 1 includes a sealed chamber 6 which contains a non-toxic oil supply 8. An air inlet tube 10 projects upwardly from the bottom of chamber 6 and extends above the oil supply 8. Inlet tube 10 communicates  
10 with an external air compressor 25 through a wall of chamber 6. An inlet orifice 12 is formed in the air inlet tube 10 so as to lie within the oil supply 8 immediately above the bottom of chamber 6. A resistor heating grid (e.g. coil) 14 extends laterally across the sealed chamber 6 and is electrically connected to a 12 volt battery 16 by means of an electric pressure switch 36. A fluid baffle 18 having a smoke outlet orifice 20 formed  
15 therein extends laterally across the sealed chamber 6 above the heating grid 14. The aforementioned smoke outlet line 2 communicates with the outlet orifice 20 through the top wall of the sealed chamber 6.

In operation, when the pressure switch 36 is closed, the battery 16 supplies  
20 current to heat the heating grid 14, and the air compressor 25 delivers air into the sealed chamber 6 via air inlet tube 10 at approximately 14 liters/minute to cause some of the oil supply 8 within the chamber to be drawn, by means of suction through inlet orifice 12 and into the air inlet tube 10. A mixture of air and oil is then blown upwardly and

outwardly from the air inlet tube 10 towards and into contact with the heating grid 18, whereby the oil is instantaneously vaporized into smoke. The rising smoke travels through the outlet orifice 20 in fluid baffle 18 for receipt by the smoke outlet line 2. Accordingly, the smoke in outlet line 2 is carried by way of the smoke supply line 4 to  
5 the fluid system to be tested so that the integrity of the system may be visually inspected for leaks depending upon the absence or presence of smoke escaping therefrom.

In accordance with the present improvement, a two-way never closing bleed-off selector valve 30 is provided to control the flow of air from the compressor 25 to either  
10 the smoke generating apparatus 1, when it is desirable to generate smoke to be delivered to the system to be tested for leaks, or to a flow meter 32, when it is desirable to supply clean (i.e. non-smoky) air to the system to be tested. The selector valve 30 is rotated to a clean air position to connect the air compressor 25 to the flow meter 32, whereby clean  
15 air will by-pass the smoke generating apparatus 1 for receipt by the system to be tested via the smoke supply line 4 when it is desirable to verify the existence and size of a potential leak in the system. Since smoke carries oil and particulate matter, it is not desirable for smoke to pass through the flow meter 32. Such smoke can cause the flow meter 32 to malfunction and eventually fail.

20 The selector valve 30 is rotated to a smoke position to cause the air compressor 25 to communicate directly with the smoke generating apparatus 1, whereby smoke can be generated to identify the specific location of a leak in the system to be tested. As will be described in greater detail hereinafter when referring to FIG. 2-4, the selector valve 30 is

also rotated to a center position (i.e. during the transition between the smoke and clean air positions) when it is desirable to bleed-off pressure that has been developed in the smoke outlet line 2 by the air compressor 25.

5           With the selector valve 30 rotated to the smoke position to connect the air compressor 25 to the smoke generating apparatus 1, air, under pressure, will be supplied to the air inlet tube 10 inside the sealed chamber 6 by way of a seven pound cracking pressure check valve 34. Pressure check valve 34 performs two different functions. In one case, the pressure check valve 34 functions as a conventional one-way check valve to  
10   block the reverse flow of oil from the smoke generating apparatus 1 to the selector valve 30. In addition, check valve 34 also prevents the backflow of oil from chamber 6 should the casing 50 be accidentally tipped. In a second case, the pressure check valve 34 establishes a back pressure in the air supply line between check valve 34 and air compressor 25. Such back pressure is required to activate the aforementioned electric  
15   pressure switch 36 which is connected to the battery 16 and which must be closed before current will be supplied from battery 16 to the heating grid 14 within the chamber 6 of smoke generating apparatus 1.

          The electric pressure switch 36 is a conventional, normally open pressure  
20   activated contact switch. When the selector valve 30 is rotated to its smoke position, the normally open electric pressure switch 36 will be closed in response to the pressure that is established in the line between check valve 34 and air compressor 25. Once switch 36 is closed, a current path will be created between the battery 16 and the heating grid 14 of



smoke generating apparatus 1 so that the droplets of oil that are blown towards heating grid 14 from oil supply 8 will be vaporized into smoke within chamber 6. However, as an important feature of this invention, when the selector valve 30 is rotated from its smoke position so as to move through the center position thereof (best described when referring to FIG. 4), an air path will be created through selector valve 30 by which to relieve the back pressure that was previously established behind check valve 34. In particular, such back pressure will be discharged through selector valve 30 to the air compressor 25 or to a soon to be described air accumulator 42. Hence, the electric pressure switch 36 will be responsive to such pressure loss, whereby to automatically return to its normally open switch condition and thereby break the current path between the battery 16 and the heating grid 14 of smoke generating apparatus 1. Accordingly, the heating grid 14 will cool and the generation of smoke will cease.

As another important feature of this invention, the smoke outlet line 2 from the sealed chamber 6 of smoke generating apparatus 1 is coupled to a pressure discharge accumulator 38 through a one pound cracking pressure check valve 40. As shown, the pressure check valve 40 is positioned upstream and between the smoke generating apparatus 1 and the system to be tested so as to be responsive to the output pressure of the smoke that is carried by the smoke outlet line 2 after selector valve 30 has been rotated to its smoke position. By virtue of the foregoing, when the smoke supply line 4 or the fluid system to be tested is partially or fully restricted, the pressure check valve 40 will open, whereby smoke and/or pressure that builds up within the smoke supply line 4 will be able to escape to the atmosphere through an orifice in the pressure discharge accumulator 38.

At the same time, the open pressure check valve 40 will allow air (including any oil products that are carried therein) to continue to circulate through the chamber 6 of smoke generating apparatus 1 in order to produce smoke therewithin. Such continued circulation will advantageously prevent the heating grid 14 of smoke generating apparatus 1 from overheating at times when the system to be tested is blocked and smoke within the outlet line 2 would otherwise be trapped.

Locating the pressure check valve 40 after the smoke producing apparatus 1, rather than prior to the air inlet tube 10 of chamber 6 (e.g. between inlet tube 10 and pressure check valve 34), avoids an early release of some or all of the pressure which would reduce or eliminate the air and oil circulation process that is otherwise achieved in the manner described above by coupling the smoke outlet line from chamber 6 to the pressure check valve 40. Thus, with the present improvement, it will still be possible to generate smoke so as to locate any leaks in the fluid system to be tested even during situations where the fluid system and/or the smoke supply line 4 is partially or completely restricted.

Locating the combination of pressure discharge accumulator 38 and pressure check valve 40 upstream from the smoke generating apparatus 1 will permit any oil products that have been vaporized by the heating grid 14 and carried through an open check valve 40 to condense and collect within the accumulator 38 during less than full flow conditions in the smoke outlet line 2. Such condensation reduces the amount of unwanted oil that would otherwise be released into the environment from the pressure

discharge accumulator 38 under abnormally high pressure conditions within the smoke outlet line 2 when the pressure check valve 40 is open. In other words, accumulator 38 collects the residue after the oil supply 8 from sealed container 6 is first vaporized by heating grid 14 into smoke and then condensed back into oil following contact with check valve 40. Without accumulator 38 to collect the oil residue, the oil carried by the smoke could build up on the outlet side of the pressure check valve 40 and eventually spill out each time that the check valve 40 would open to release pressure. Such oil spillage could be undesirably encountered at the exterior of the casing 50 in which the smoke generating apparatus 1, selector valve 30 and pressure check valve 40 are all housed and transported from place to place.

At such time when the selector valve 30 is rotated to its clean air position (when no smoke is being generated by apparatus 1), an air path is established between compressor 25 and a pre-meter air accumulator 42. Air accumulator 42 is preferably a hollow chamber or air damper that functions to reduce or dampen the fluctuation to which flow meter 32 would be subjected that might alter the reading of flow meter 32 as a consequence of the pulsations that are common to a piston-type air compressor, such as that which has been shown and described herein, and the opening and closing of a soon to be described check valve 44. In this same regard, it would be possible to eliminate the air accumulator 42 altogether if the air compressor 25 were replaced by a non-pulsating air pump. However, a pulsating piston-type air compressor 25 is preferable because it is known to be reliable and readily available for use in the present invention.

A one-half pound check valve 44 is coupled to the air accumulator 42. Check valve 44 functions to relieve excess pressure within the clean air supply line 46 when clean air is supplied via flow meter 32 and the system to be tested or the smoke supply line 4 is partially or fully restricted. It is important that the check valve 44 be positioned behind (i.e. downstream from) the flow meter 32. During clean air operation, with selector valve 30 rotated to its clean air position, if check valve 44 were located ahead of (i.e. upstream from) flow meter 32, then the flow meter 32 would continue to meter clean air passing therethrough even if the system to be tested or the smoke supply line 4 were blocked.

Connected in the clean air supply line 46 which runs from flow meter 32 to smoke supply line 4 is a directional check valve 48. Check valve 48 limits the flow of clean air from air compressor 25 to a single direction away from flow meter 32 so that smoke produced by smoke generating apparatus 1 will be unable to pass through the clean air supply line 46 to contaminate the flow meter 32 and loose pressure through check valve 44 which would undesirably reduce the efficiency of operation.

On the other hand, to maximize the efficiency of the smoke and clean air generating machine of this invention, it is important that the check valve 44 on the clean air side have a lower cracking or threshold pressure (e.g. one-half pound) than the cracking pressure (e.g. one pound) of the check valve 40 on the smoke side. As previously described, if the system to be tested or the smoke supply line 4 were partially or completely restricted after selector valve 30 is rotated to its clean air position, any

excess pressure that is built up in the clean air supply line 46 would escape through check valve 44 of air accumulator 42. However, if the cracking pressure of check valve 40 were less than the cracking pressure of check valve 44, then flow meter 32 will continue to meter air flow therethrough even during such high pressure conditions. By virtue of the present improvement, if the system to be tested or the smoke supply line 4 were blocked when the selector valve 30 is rotated to its smoke position, then the smoke generated by apparatus 1 will escape through check valve 40, since the directional check valve 48 will not allow the back flow of smoke through the clean air supply line 46 and towards flow meter 32.

Although the smoke generating apparatus 1 has been described above as receiving air under pressure from an air compressor 25, it is to be understood that gases other than air may be supplied to the air inlet tube 10 of apparatus 1 to cause a mixture of such gas and oil to be blown towards the heating grid 14. More particularly, testing the integrity of the evaporative system in a motor vehicle is now required by the Environmental Protection Agency in many states. It has become essential to be able to verify if the evaporative system has a leak and then identify the location of the leak. As an alternative to pressurized air, carbon dioxide or nitrogen gas from a pressure and flow regulated tank or bottle 60 can be used because of their non-flammable and inert characteristics. That is to say, smoke carried by nitrogen gas would be relatively safe for testing the evaporative system of a motor vehicle which lies in a generally volatile environment of potentially explosive hydrocarbon vapors. Accordingly, the ability to produce smoke with nitrogen gas would provide a safe and efficient means for locating a leak in the evaporative system

of a motor vehicle. Moreover, producing smoke with nitrogen gas rather than air would enable a variety of high pressure systems (e.g. an air brake system) to be tested at high operating temperatures but without the inherent risks of an explosion.

5           What is even more, other sources of air under pressure, other than air compressor 25, may be employed to blow the oil towards the heating grid 14. For example, conventional shop air such as that used by an automotive repair facility may be substituted for compressor 25.

10           The advantage provided by the smoke and clean air generating machine of this invention is not only the ability to indicate the precise location of a leak (when selector switch 30 is rotated to the smoke position), but also to first verify whether the system to be tested has a leak in need of repair (when selector switch 30 is rotated to the clean air position). More particularly, the flow meter 32 that is connected in the clean air supply  
15 line 46 is a non-regulating flow meter that has a ball indicator to provide a visual reading when the system to be tested has a leak that is of sufficient size to warrant repair. Flow meter 32 is first initialized to a flow rate setting that corresponds to a leak size in the fluid system of 1 millimeter in diameter, a size which is generally considered in the industry to represent the standard tolerance level of a fluid system before the repair of a leak is  
20 required. Of course, the initial setting of flow meter 32 could change in the event that the tolerance standards of fluid systems subjected to leaks also change.

Once the selector valve 30 is rotated to its clean air position to connect air compressor 25 to flow meter 32, should the fluid system have a leak size which is in tolerance (i.e. less than 1 millimeter) then the reading of flow meter 32 will be at or below the initialized flow rate, and no repair will be necessary. However, should the fluid system have a leak, the size of which is larger than 1 millimeter, then the reading of flow meter 32 will be above the initialized flow rate, such that the leak must be located and repaired. At this point, the selector valve 30 is rotated from its clean air position to its smoke position, whereby a supply of smoke is delivered from the sealed chamber 6 of smoke generating apparatus 1 to the system to be tested in the manner described above.

Turning now to FIGs. 2-4 of the drawings, details of the 2-way bleed-off selector valve 30 are now provided. FIG. 2 shows the selector valve 30 having a manually controlled knob 50 rotated to the clean air position in order to connect the air compressor 25 to the clean air side of the smoke and clean air generating machine of this invention so that a supply of clean air will be delivered to the system under test via the flow meter 32 in order to verify the presence of a leak having sufficient size to warrant repair. In this same regard, the air compressor 25 is disconnected from the smoke generating apparatus 1.

FIG. 3 shows the knob 52 of selector valve 30 rotated 180 degrees from the clean air position of FIG. 2 to the smoke position to connect the air compressor 25 to the smoke side of the smoke and clean air generating machine so that a supply of air will be delivered to the smoke generating apparatus 1. Smoke generated from the sealed

W

chamber 6 of apparatus 1 is supplied to the system under test via smoke outlet line 2 in order to detect the precise location of the leak in need of repair depending upon a visual observation of smoke escaping through the leak. In this same regard, the air compressor 25 is disconnected from the flow meter 32.

5

FIG. 4 shows the knob 52 of selector valve 30 momentarily rotated through a center or neutral position during the transition of knob 52 from the smoke position of FIG. 3 to the clean air position of FIG. 2. In this case, an air path is established through selector valve 30 from the check valve 34 to the air compressor 25 and/or the air accumulator 42 in order to bleed off air pressure from pressure switch 36. As previously described, pressure switch 36 is responsive to such pressure loss and will return to its normally closed condition, whereby to disconnect the battery 16 from the heating grid 14 of smoke generating apparatus 1 so as to allow the heating grid to safely cool and thereby terminate the generation of smoke.

10  
15

It may be appreciated that in a conventional selector valve, the center position thereof would typically allow no air to flow in either direction through the valve. However, selector valve 30 of the present invention is a never closing valve such that in its center position, the smoke side of the smoke and clean air generating machine is momentarily placed into communication with the clean air side whereby air pressure will be bled from the smoke side to cause a drop in pressure so that heating grid 14 will cool and no smoke will be generated. As described above, such bleeding off of the air pressure from the smoke side occurs only when selector valve 30 is moved through its

20

17



center or neutral position and, unlike conventional valves, permits the aforementioned communication between the smoke and clean air sides to disconnect heating grid 14 from battery 16.

5

WE CLAIM:

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000